

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : C07D 301/08		A1	(11) International Publication Number: WO 00/20404
			(43) International Publication Date: 13 April 2000 (13.04.00)
(21) International Application Number: PCT/EP99/07506		(74) Agent: COLMER, Stephen, Gary; Mathys & Squire, 100 Gray's Inn Road, London WC1X 8AL (GB).	
(22) International Filing Date: 6 October 1999 (06.10.99)			
(30) Priority Data: 09/167,329 7 October 1998 (07.10.98) US		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(71) Applicant (for all designated States except MN): ARCO CHEMICAL TECHNOLOGY L.P. [US/US]; Two Greenville Crossing, Suite 238, 4001 Kennett Pike, Greenville, DE 19807 (US).			
(71) Applicant (for MN only): LYONDELL CHEMIE TECHNOLOGIE NEDERLAND B.V. [NL/NL]; Theemsweg 14, 3197 KM Botlek, Rotterdam (NL).			
(72) Inventors: COCHRAN, Robert, N.; 310 Carlyle Road, West Chester, PA 19382 (US). JUBIN, John, C., Jr.; 144 Summit House, West Chester, PA 19382 (US). LIEPA, Mark, A.; 303 Colonial Drive, Exton, PA 19341 (US). NEDWICK, Robert; 226 Foxcroft Road, Broomall, PA 19008 (US). PITCHAI, Rangasamy; 207 Fowler Drive, West Chester, PA 19382 (US). WENTZHEIMER, W., Wayne; 4736 Cavalcade Drive, Grands Rapids, MI 49546 (US).		Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(54) Title: PROPYLENE OXIDE PRODUCTION			
(57) Abstract <p>An integrated process is provided for the production of propylene oxide from propane wherein propane is dehydrogenated to propylene and hydrogen and the resulting propylene, propane, and hydrogen mixture together with added oxygen is reacted over a palladium on titanium silicillite catalyst to form propylene oxide, the molar ratio of oxygen to hydrogen in the reaction feed being at least about 2/1.</p>			

Best Available Copy

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

PROPYLENE OXIDE PRODUCTIONBackground of the Invention1. Field of the Invention

5 The present invention relates to the production of propylene oxide by a process wherein propane is dehydrogenated and the product mixture comprised of propylene, propane and hydrogen from the dehydrogenation, together with added oxygen, is reacted to form propylene oxide.

2. Description of the Prior Art

10 Integrated processes have been proposed wherein propane is dehydrogenated to form propylene with the propylene being epoxidized, using a hydroperoxide or hydrogen peroxide, to form propylene oxide. See, for example, U.S. Patent 5,599,956. Such prior procedures have required the costly separation of propylene from hydrogen in the dehydrogenation product prior to the epoxidation of the propylene to propylene oxide.

20 In addition, methods have been proposed such as suggested in U.S. Patents 4,990,632 and 5,008,412 wherein propane is dehydrogenated and the resultant propylene is oxidized to propylene oxide using a catalyst such as silver oxide; oxygen is eliminated by oxidation from the recycle stream.

25 Further, in EP 0850936 a process is described wherein propane is dehydrogenated, oxygen is added to the dehydrogenation product and the resulting mixture is epoxidized over a gold catalyst with oxygen being eliminated from the recycle stream.

30 The instant invention represents a significant improvement over prior procedures in that the mixture of propylene, propane, and hydrogen from the propane dehydrogenation is used, without separation of the components, to form propylene oxide over a Pd/TS-1 catalyst with recycle of oxygen to the epoxidation.

Summary of the Invention

35 In accordance with the invention, propane is dehydrogenated to a dehydrogenation product comprised of propylene, propane, and hydrogen. The mixture of propylene, propane, and hydrogen together with added oxygen and such

additional hydrogen as may be needed is contacted with an epoxidation catalyst such as a Pd/TS-1 catalyst at epoxidation conditions to form propylene oxide.

Brief Description of the Drawing

5 The accompanying drawing illustrates schematically an embodiment of the invention.

Detailed Description

Referring to the drawing, net feed propane is introduced into dehydrogenation zone 101 via line 1 along with recycle propane which is introduced via line 2. In zone 101 the propane is dehydrogenated to form propylene and hydrogen. Commercially practiced technology for this dehydrogenation step is represented for example, by the UOP OLEFLEX process or the CATOFIN process of United Catalysts/Lummus Crest.

15 The dehydrogenation reaction product mixture comprised of unreacted propane, propylene and hydrogen is removed from dehydrogenation zone 101 via line 3, combined with recycle vapor via line 4 and the mixture passed via line 5 to oxygen mixing station 102 wherein the mixture is mixed with oxygen fed via line 6 and hydrogen fed via line 7. The resulting vapor feed passes via line 8 to epoxidizer 103.

20 Also fed to epoxidizer 103 via line 9 is a liquid C₃'s recycle stream. It is preferred to carry out the epoxidation using a solvent such as methanol and this is introduced via line 10 to the epoxidizer.

25 In zone 103 propylene, hydrogen and oxygen are contacted at reaction conditions with an effective catalyst to produce propylene oxide. The epoxidation reaction is, itself, a known reaction as shown, for example, in Japanese Kokai No. 4-352771 where the reaction of propylene, hydrogen and oxygen over a catalyst comprised of a Group VIII metal and a crystalline titanasilicate to form propylene oxide is described.

30 It is important that a substantial molar excess of oxygen relative to hydrogen be fed to the epoxidation in order to achieve a reasonable reaction rate and selectivity to propylene oxide. Generally the O₂/H₂ mol ratio fed to zone 103 should be 2/1 or higher, eg. 2/1 - 5/1.

The reaction mixture from epoxidation zone 103 passes via line 11 to separation zone 104. In zone 104, the readily condensable propylene oxide and solvent are separated from the lighter materials comprised of propane, propylene, oxygen and hydrogen. The propylene oxide and solvent mixture is removed from zone 104 and passes via line 12 to separation zone 107. This mixture is distilled in zone 107 and an overhead product propylene oxide stream is removed via line 13 and transferred to zone 106 wherein by known procedures purified propylene oxide is recovered via line 14 and lighter fuel value materials are recovered via line 15.

The light materials from separation zone 104 pass via line 16 to C₃ recovery zone 108 where lighter materials are separated as by distillation from the C₃ components. Lights which have a significant fuel value are recovered via line 17 while the propane/propylene and excess O₂ and H₂ vapor components are recycled via lines 2 and 4. Methane is introduced via line 18 to prevent flammability of the fuel mixture.

Most of the C₃ stream is recycled to epoxidation as above described. A minor amount, eg. about 4% of the stream is recycled via line 2 to dehydrogenation zone 101 as above indicated.

A liquid propylene and propane stream is recycled via line 9 to epoxidation zone 103.

From separation zone 107, a bottoms stream comprised of solvent passes via line 19 to separation zone 105 from which solvent is removed via line 10 and recycled to epoxidation zone 103. A stream comprised of water and fuel value organics is removed via line 20. Make up solvent is introduced through line 21 into the system.

It can be seen that the process of the present invention is distinctly advantageous in that costly separation of the components of the dehydrogenation reaction mixture as previously thought necessary is avoided. Propylene oxide is produced in high efficiency and with substantial economics of operation.

Both the CATOFIN and OLEFLEX processes are described in Kirk-Othmer "Encyclopedia of Chemical Technology", Fourth Edition, Vol 20, P. 259-260 (1996). As described therein, the CATOFIN process uses a relatively inexpensive and durable chromium oxide-alumina as catalyst. This catalyst can be easily and rapidly regenerated under severe conditions without loss in activity. To improve propylene selectivity and to increase the propane conversion, this technology uses a vacuum. Dehydrogenation is carried out in the gas phase over fixed beds. Because the catalyst cokes up rapidly, five reactors are typically used. Two are on-stream while two are being regenerated and one is being purged. The reactors are cycled between the reaction and the reheat/regeneration modes, and the thermal inertia of the catalyst controls the cycle time, which is typically less than 10 minutes.

The OLEFLEX process uses multiple side-by-side radial flow moving-bed reactors connected in series. The heat of reaction is supplied by preheated feed and interstage heaters. The gas-phase reaction is carried out over a catalyst, platinum supported over alumina, under very near isothermal conditions. Other known dehydrogenation procedures can be used.

The dehydrogenation is equilibrium limited and per pass yield of propylene is quite low. Accordingly the dehydrogenation effluent contains substantial amounts of unreacted propane which, in preferred practice serves as a ballast gas in subsequent steps. Generally, about 1 mol of hydrogen is contained in the dehydrogenation effluent per mol of propylene.

Epoxidation in zone 103 is carried out at reaction temperatures of 50 to 100°C, and preferably 50 to 70°C. Pure oxygen can be used as one of the starting materials for the reaction.

The amounts of the several starting materials contained in the gas can vary. Generally 10 to 50 vol % propylene, 5 to 20 vol % hydrogen, and 10 to 50 vol % oxygen are suitable on a ballast gas free basis with the O₂/H₂ ratio being at least

2/1. From the standpoint of safety, it is desirable for the contained amount of the several starting materials to be outside of the explosive range. Preferably propane is used as a ballast gas although other gases such as nitrogen, methane, and the like are useful.

System pressures in the range 50 to 500 psia are suitable.

In the epoxidation, a catalyst comprising a Group VIII metal and a crystalline titanasilicate is used. The titanasilicate referred to here is obtained by substitution of a portion of the silicon which forms the crystal lattice of "Silicalite" (crystalline SiO_2 having a zeolite structure, developed by E. M. Flanigen (Nature, 271, 512 (1978)) mainly with titanium. The titanasilicate may be synthesized by any desired method; an example of synthesis is disclosed in Japanese Laid-Open Patent application 56-96720. The amount of titanium contained in said titanasilicate may be defined as the silica/titania ratio (molar), and said silica/titania ratio should be 5 to 200. If the titanium content is too low the activity of the catalyst will be insufficient. Components of the titanasilicate are not restricted to titanium; one or more additional elements such as boron, aluminum, phosphorus, vanadium, chromium, manganese, iron, gallium, or zirconium may also be contained therein.

The prepared titanasilicate may be used without modification, or molded. It is common to use a binder when preparing a molded form; there are no restrictions regarding the type of binder, which may be silica, alumina, or the like. In the catalyst any of the Group VIII metals may be used. Typical examples include palladium, platinum, iridium, rhodium, ruthenium, and the like; palladium is particularly desirable. The Group VIII metal may be supported on the crystalline titanasilicate, or first supported on silica, alumina, activated carbon or the like and then physically mixed with the titanasilicate. There are no particular restrictions regarding the starting material to be supported when supporting a Group VIII metal; examples include

palladium(II) chloride, tetraaminepalladium(II) chloride, and palladium(II) acetate when palladium is used. There are no restrictions regarding the method for supporting these metals on the titanosilicate; an immersion method or the like may be used.

The Group VIII metal content, with respect to the titanosilicate, should be 0.1 to 10 wt % as metal atoms. Efficacy will be diminished if the content falls below 0.1 wt %, and amounts in excess of 10 wt % are undesirable from an economic standpoint. When the Group VIII metal is supported on titanosilicate using an immersion process, the catalyst may be baked and/or reduced prior to use. Baking may be performed under a stream of an inert gas or an oxygen-containing gas. There are no particular restrictions regarding baking temperature and duration, but baking at 100 to 700°C for 30 minutes to 24 hours is satisfactory. When reduction is performed, there are no particular restrictions regarding the reducing agent or the reduction temperature and duration as long as the metal component is reduced; reduction at room temperature to 500°C for 30 minutes to 24 hours using hydrogen as a reducing agent is satisfactory.

The prepared catalyst may be used without modification or by adding a diluent such as silica or alumina prior to use in reactions. The prepared Group VIII metal-supporting zeolite catalyst may be reduced under a hydrogen-containing gas flow prior to use in reactions.

If necessary, a solvent such as water, alcohols having a carbon number of 6 or less, ethers, esters, ketones, glycols, carboxylic acids and the like may be used. Methanol is especially preferred.

The reaction process may be of a continuous flow, semi-batch, or batch type; a continuous flow process is preferable from a productivity standpoint.

The following example illustrates an embodiment of the invention with reference to the attached drawing. Table 1 shows the flow rates of the various components for the indicated process streams.

Referring to the drawing, net feed propane is introduced into dehydrogenation zone 101 via line 1 along with recycle propane which is introduced via line 2. In zone 101 the propane is dehydrogenated to form propylene and hydrogen. The dehydrogenation is carried out by the known CATOFIN process of United Catalysts/Lummus Crest. The catalyst is chromic oxide on alumina, the dehydrogenation temperature is 525-677°C and pressure is 0.1-0.7 atmospheres absolute. LHSV is less than 1 hr⁻¹.

In reactor 1 conversion of propane is about 60% and the selectivity to propylene is about 85%.

The dehydrogenation reaction product mixture comprised of unreacted propane, propylene and hydrogen is removed from dehydrogenation zone 101 via line 3, combined with a recycle oxygen/hydrogen/propane/propylene vapor stream via line 4 and the mixture passed via line 5 to oxygen mixing station 102 wherein it is mixed with oxygen fed via line 6 and hydrogen fed via line 7. The resulting vapor feed is passed via line 8 to epoxidizer 103.

Also fed to epoxidizer 103 via line 9 is a liquid propylene recycle stream. It is preferred to carry out the epoxidation using a solvent such as methanol and this is introduced via line 10 to the epoxidizer.

In zone 103 propylene, hydrogen and oxygen are contacted at reaction conditions with an effective catalyst to produce propylene oxide. The epoxidation reaction is, itself, a known reaction as shown, for example, in Japanese Kokai No. 4-352771 where the reaction of propylene, hydrogen and oxygen over a catalyst comprised of a Group VIII metal and a crystalline titanasilicate to form propylene oxide is described.

Generally speaking, slurry techniques wherein the solid catalyst is slurried in an appropriate liquid or fixed bed epoxidation procedures can be employed. In the embodiment herein described, the catalyst is a palladium on titanium silicalite as described in Japanese Kokai No. 4-352771. A fixed bed reactor of the type described in U.S. Patent 5,466,836 is employed with downflow of the reactants.

Epoxidation temperature is about 65°C (generally 50-95°C is suitable) and pressure is about 230 psia (200-300 psia is a useful range). About 22% propylene conversion with 70% molar selectivity to propylene oxide is achieved.

5 The reaction mixture from epoxidation zone 103 passes via line 11 to separation zone 104. In zone 104, the readily condensable propylene oxide and solvent are separated from the lighter materials comprised of propane, propylene, oxygen and hydrogen. The propylene oxide and solvent are removed from
10 zone 104 and passed via line 12 to separation zone 107. The mixture is distilled in zone 107 and an overhead product propylene oxide stream is removed via line 13 and transferred to zone 106 wherein by known procedures purified propylene oxide is recovered via line 14.

15 The light materials from separation zone 104 pass via line 16 to C₃ recovery zone 108 where a purge gas containing the light materials is separated as by distillation from the C₃ components. Lights which have a significant fuel value are recovered via line 17 while the propane/propylene components
20 and unreacted oxygen and hydrogen are recycled. Methane is introduced via line 18 to control flammability.

The C₃ components are resolved by known procedures (not shown) with a propane stream being recycled via line 2 to dehydrogenation 101 as above indicated.

25 From separation zone 107, a bottoms stream comprised of solvent passes via line 19 to separation zone 105 from which solvent is removed via line 10 and recycled to epoxidation zone 103. A stream comprised of water and fuel value organics is removed via line 20. Make up solvent is introduced through
30 line 21.

For purposes of simplicity, the attached drawing illustrates various operations as taking place in a single zone. Actually, however, in many of the steps a plurality of operations such as various separations are suitably employed
35 as will be apparent to those skilled in the art.

The following Table 1 shows the appropriate flow rates of the various components of the process streams.

Table 1

Component, lbs/hr	Stream						
	1	2	3	4	6	7	5
Propylene		10332	92329	229594			321923
Propane	75291	92985	67215	2066342			2133556
Propylene Oxide							
Oxygen				116327	73251		116327
Hydrogen			3905	9694		3371	13599
Water							
Methanol							
Fuel			15159				

Table 1 continued

Component, lbs/hr.	Stream										
	9	10	11	13	14	15	20	21			
Propylene	57398		297324								
Propane	516585		2675912								
Propylene Oxide			79264	79264	75301	3963					
Oxygen	29082		153062								
Hydrogen	2423		12755								
Water		10000	59199				49199				
Hydrogen Peroxide											
Methanol		2190727	2195117	7580			4390	4390			
Fuel			15159			7580					

Table 1 continued

Stream						
Component lbs/hr	12	19	16	17	18	
Propylene			297324			
Propane			2675912			
Propylene Oxide	79264					
Oxygen			153062	7653		
Hydrogen			12755	638		
Water	59199	59199				
Hydrogen Peroxide						
Methanol	2195117	7580				
Fuel	7580		7580	56123	48543	

5


10

11

15

CLAIMS:

1. A process for the preparation of propylene oxide which process comprises:
 - a) dehydrogenating propane to a dehydrogenation product mixture comprised of propylene, propane, and hydrogen, and
 - b) reacting the said mixture of propylene, propane, and hydrogen together with added oxygen over a palladium on titanium silicilite catalyst to form propylene oxide, the oxygen fed to the epoxidation being in a molar excess, relative to hydrogen.
2. A process according to Claim 1 wherein the product mixture of step (a) is used, without separation of its components, as feed to step (b).
3. A process according to Claim 1 or 2 wherein the molar ratio of oxygen to hydrogen in the reaction feed is at least 2/1.
4. A process according to Claim 2 wherein the molar ratio of oxygen to hydrogen in the reaction feed is in the range 2/1 to 5/1.
5. A process according to any preceding claim wherein the reaction feed comprises from 10 to 50 vol% propylene; 5 to 20 vol% hydrogen and 10 to 50 vol% oxygen.
6. A process according to any preceding claim wherein unreacted oxygen is recycled to the said reaction step.
7. A process according to any preceding claim wherein the epoxidation is effected at a temperature from 50°C to 100°C.
8. A process according to any preceding claim wherein the titanasilicate catalyst has a silica/titania molar ratio from 5 to 200.
9. A process according to any preceding claim wherein the reaction conditions involve use of a solvent.
10. A process of claim 9 wherein the solvent is methanol.



INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 99/07506

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 C07D301/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 C07D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 850 936 A (AGENCY OF INDUSTRIAL SCIENCE AND TECHNOLOGY) 1 July 1998 (1998-07-01) cited in the application column 5, line 42 - line 52 column 8, line 36 - line 49; claims; examples ---	1-10
Y	US 5 008 412 A (RAMACHANDRAN ET. AL.) 16 April 1991 (1991-04-16) cited in the application column 5, line 33 - line 48; claims; table 1 ---	1-10
Y	US 4 990 632 A (RAMACHANDRAN ET. AL.) 5 February 1991 (1991-02-05) column 7, line 20 - line 28; claims; tables I,,II ---	1-10
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

3 February 2000

Date of mailing of the international search report

14/02/2000

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Helps, I

INTERNATIONAL SEARCH REPORT

Int. onal Application No
PCT/EP 99/07506

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	R. MEIERS ET. AL.: "Synthesis of Propylene Oxide from Propylene, Oxygen, and Hydrogen Catalysedby Palladium-Platinum-Containing Titanium Silicalite " JOURNAL OF CATALYSIS, vol. 176, 1998, pages 376-86, XP000872192 whole article -----	1-10

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/EP 99/07506

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 850936 A	01-07-1998	JP 10237055 A	08-09-1998
		US 5929258 A	27-07-1999
US 5008412 A	16-04-1991	US 4849537 A	18-07-1989
		AU 2889489 A	10-08-1989
		EP 0328280 A	16-08-1989
		JP 2001449 A	05-01-1990
		TR 25102 A	28-09-1992
US 4990632 A	05-02-1991	US 4849538 A	18-07-1989
		AT 90336 T	15-06-1993
		AU 2999389 A	28-09-1989
		EP 0336592 A	11-10-1989
		JP 2004753 A	09-01-1990
		JP 2685279 B	03-12-1997
		KR 145305 B	15-07-1998

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.